

ComfortBreeze®

Wall Mount Ceiling & Floor

AHU

Window Air Cooled Split



Quality built-in inverter technology



Wall Mount Whether it's a livingroom, bedroom or office, the Air Conditioner you need. Mini Sp Series will provide the endurance and reliability you need.

Models: 9CR9VA1 - 12CR9VA1

Requires professional installation - R410A
Consult your Air Conditioning professional

Sal del Calor Ahorrando Energía con tu Unidad Inverter

Financiamiento Disponible
Toll Free 1.855.MGD.AIRE
1.855.643.2473

Comfort Breeze Inverters

MODEL		CBZ/CBZO-9CR9VA1	CBZ/CBZO-12CR9VA1	CBZ/CBZO-18CR9VA1	CBZ/CBZO-24CR9VA1	
Power supply		V / Ph / Hz 220-230V / 60Hz / 1Ph				
Cooling	Capacity	BTU/H	9k (2,250~11,500)	12k (4,000~13,500)	18k (5100~20000)	24k (12,000~25,000)
	Input	W	820	1100	1740	2237
	SEER	-	17	17	16.5	16.5
	Rated current	A	3.7	4.8	8.3	9.7
Moisture Removal		L/H	1.0	1.2	1.8	2.6
Max. Input Consumption		W	1900	2000	2900	3200
Max. Current		A	8.0	8.5	13.0	14.5
Compressor	Type	ROTARY				
	Input	W	680	855	995	1150
	Rated Current (RLA)	A	4.6	5.3	6.87	9.7
	Locked Rotor Amp (LRA)	A	10	10	----	----
	Refrigerant Oil / Oil Charge	ml	ESTER OIL VG74/480	ESTER OIL VG74/480	ESTER OIL VG74/480	ESTER OIL VG74/500
Fan Motor	Input	W	32.5	43	58.5	82/79/58
	Capacitor	uF	1.2	1.5	1.5	3.0
	Speed (Hi/Mi/Lo)	R/min	1170 / 1000 / 800	1200 / 1000 / 850	1200 / 1000 / 880	1285 / 1245 / 1040
Indoor Coil	a.Number Of Rows		2/1	2/1	2	2
	c.Fin Spacing	mm	1.2	1.2	1.3	1.3
	d.Fin Type (code)	Hydrophilic aluminum				
	g.Number Of Circuits		2	2	4	4
Indoor Air Flow (Hi/Mi/Lo)		CFM	335/290/240	365/306/265	441/371/324	677/647/547
Indoor Noise Level (Hi/Mi/Lo)		dB(A)	36/34/30	38/34/30	40/35/30	50/48/46
Indoor Unit	Dimension(W*D*H)	mm	845x165x290	850x165x290	995x200x295	1084x221x320
	Packing (W*D*H)	mm	920x240x365	920x240x365	1070x370x275	1160x400x315
	Net/Gross Weight	Kg	8.5 / 10.5	8.5 / 10.5	11.5 / 14	14 / 18
	Input	W	70/62	75/66	119/96	166/105
	Capacitor	uF	2.5 / 6.0	2.5 / 6.0	2.5	2.5
	Speed	r/min	940 / -- / 835	940 / -- / 835	860 / -- / 680	800/600
Outdoor Air Flow		m3/h	1650	1900	2200	2700
Outdoor Noise Level		dB(A)	53	55	58	56
Outdoor Unit	Dimension(W*D*H)	mm	700x235x535	780x250x540	760x285x590	845x320x700
	Packing (W*D*H)	mm	815x325x580	910x335x585	887x355x645	965x395x755
	Net/Gross Weight	Kg	25 / 27	28 / 30	34.5 / 37	44 / 48
Refrigerant Type		g	R410A/570g	R410A/700g	R410A/980g	R410A/1180g
Design Pressure		MPa	4.2/1.5	4.2/1.5	4.2/1.5	4.2/1.5
Refrigerant Piping	Liquid Side / Gas Side	mm(inch)	Φ6.35/Φ9.52(1/4"/3/8")	Φ6.35/Φ12.7(1/4"/1/2")	Φ6.35/Φ12.7(1/4"/1/2")	Φ9.52/Φ16(3/8"/5/8")
	Max. Refrigerant Pipe Length	m	20	20	25	25
	Max. Level Difference	m	8	8	10	10
Thermostat Type		Remote Control				

Product specifications subject to change without notice.



Sal del Calor Ahorrando Energía con tu Unidad Inverter

Financiamiento Disponible
Toll Free 1.855.MGD.AIRE
1.855.643.2473